

# ENDURO PRO



Satin Cypress Metallic / Ion Metallic

Das Enduro Pro war schon immer hart im Nehmen – daran hat sich auch jetzt nichts geändert. Mit 170 Millimetern Federweg bekommst du die beste Downhill-Performance, mit der du auch noch überraschend effizient bergauf kletterst. Die erstklassige RockShox Federung, die SRAM Maven Silver 4-Kolben-Bremsen, die SRAM Eagle X0 T-TYPE AXS Schaltung und der Roval Traverse HD i9 Laufrad-satz runden die Ausstattung ab.

ENDURO	S2	S3	S4	S5
Stack (mm)	616	620	629	638
Reach (mm)	437	464	487	511
Head-Tube Length (mm)	95	100	110	120
Head-Tube Angle (degrees)	63.9	63.9	63.9	63.9
B-B Height (mm)	354	354	354	354
B-B Drop (mm)	21	21	21	21
Trail (mm)	132	132	132	132
Fork Length, Full (mm)	581	581	581	581
Fork Rake/Offset (mm)	46	46	46	46
Front-Center (mm)	777	806	833	862
Chainstay Length (mm)	442	442	442	442
Wheelbase (mm)	1217	1246	1274	1302
Top-tube Length (horizontal - mm)	591	619	644	670
Seat-Tube Length (mm)	400	420	440	465
Seat-Tube Angle (degrees)	76	76	76	76

## SPECS

## Technische Änderungen vorbehalten.

Rahmen	FACT 11m carbon chassis and rear-end, 29 S-Sizing Enduro Race Geometry, SRAM Universal Derailleur Hanger, SWAT™ Door integration, threaded BB, internal cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, 170mm of travel
Dämpfer	RockShox Vivid Ultimate, Ride Dynamics Trail Tune, adjustable hydraulic bottom out, adjustable rebound and high/low speed compression, 205x60, Trunnion
Gabel	RockShox Zeb Ultimate, Charger 3.1 damper, 15x110mm, 44mm offset, 170mm of travel
Vorbau	Industry 9 Mountain stem, 35mm clamp, 40mm length
Griffe	Deity Lockjaw
Lenker	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S2: 780mm; S3-S5: 800mm
Bremse Vorne	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 220mm
Bremse Hinten	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 200mm
Schaltwerk	SRAM X0 Eagle Transmission Derailleur
Schalthebel	SRAM AXS POD Controller
Kassette	SRAM X0 Eagle Transmission Cassette, 12spd, 10-52t
Kurbelgarnitur	SRAM X0 Eagle Crankset, 32T ring, S2-S3:165mm, S5-S6: 170mm
Innenlager	SRAM DUB, BSA 73mm Wide, Threaded
Kette	SRAM X0 Eagle Transmission Flattop Chain
Felgen	Roval Traverse HD, hookless carbon, 30mm inner width, tubeless ready
Vorderradnabe	Industry 9 1/1, 15x110mm, 28h
Hinterradnabe	Industry 9 1/1, 12x148mm, 32h
Speichen	Sapim D-Light
Vorderreifen	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Hinterreifen	Butcher, GRID GRAVITY casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
Schläuche	Standard, Presta Valve
Sattelstütze	Bike Yoke, Revive Max, 34.9, S2-S3: 160mm, S4-S5: 185mm
Sattelstützklemme	Alloy, 38.6mm
Sattel	Bridge Expert with MIMIC, Hollow Ti rails, S2: 155mm, S3-S5: 143mm
SWAT	SWAT internal downtube storage
Gewicht	16.04 kg (Größe: S4)

SKU	BESCHREIBUNG	FARBE	GRÖSSE
93625-3002	Enduro Pro	Satin Cypress Metallic / Ion Metallic	S2
93625-3003			S3
93625-3004			S4
93625-3005			S5